


MOUNTING OPTIONS FOR EVOLVE COLUMN SYSTEM SERIES

The EVOLVE WMK (wall-mount kit) and EVOLVE TM-B (truss-mount bracket) enable users to mount the column speaker array of an EVOLVE 30M, 50 or 50M system at a greater height or distance from its dedicated subwoofer than the provided distance pole allows.

The kits allow users more acoustic and aesthetic flexibility when using an EVOLVE system. For example, the array can be wall-mounted or truss-mounted at an increased height for a longer throw into the listening area; the subwoofer can be stowed away from the array for a more streamlined stage setup or to save space.

Four WMK options are available, equipped with either Phoenix-style / Euroblock or NL4 connectors and finished in black or white. The TM-B is equipped with NL4 connectors and comes in black.





EVOLVE WMK

(WALL-MOUNT KIT)

- Innovative mounting system for simple and secure installation of EVOLVE 30M, EVOLVE 50 and EVOLVE 50M systems, available in black or white.
- Sturdy wall-mount bracket with 15° of downward tilt and 45° of left and right adjustment.
- Subwoofer and column adapters available with either Phoenix-style / Euroblock (internally secured PCB screw terminal blocks) or NL4 connectors.
- Use correctly rated speaker cable for optimal performance: wire gauges 1.5 mm² - 2.5 mm² (AWG16 - AWG14).
- Includes: wall-mount bracket, subwoofer amplifier and input cover, column speaker adapter, subwoofer adapter, secondary auxiliary support cable, installation manual, two rubber grommets (Phoenix kits only).



EVOLVE-WMK-PB

Wall-mount kit, Phoenix, black F.01U.392.641



EVOLVE-WMK-NB

Wall-mount kit, NL4, black F.01U.392.643



EVOLVE-WMK-PW

Wall-mount kit, Phoenix, white F.01U.392.642



EVOLVE-WMK-NW

Wall-mount kit, NL4, white F.01U.392.644

EVOLVE TM-B

(TRUSS-MOUNT BRACKET)

- Innovative mounting system for simple and secure installation of EVOLVE 30M, EVOLVE 50 and EVOLVE 50M systems, available in black only.
- Sturdy truss-mount bracket works with M10 threaded studs found on common truss clamps (truss clamps not included).
- Subwoofer and column adapters equipped with NL4 connectors.
- Use correctly rated speaker cable for optimal performance: wire gauges 1.5 mm² - 2.5 mm² (AWG16 - AWG14).
- For use with truss clamps rated for WLL= 20 kg (44 lb) SF = 5:1.
- Includes: truss mount, column speaker adapter, subwoofer adapter, subwoofer amplifier and input cover, secondary auxiliary support cable, installation manual.



EVOLVE-TM-B

Truss-mount bracket, black F.01U.395.777

